

ORTAC METAL CABLE GLANDS SERIES



METAL CABLE GLANDS STANDARD TYPE SILICONE SEAL


TECHNICAL DETAILS

Material

Cap nut	: Brass with nickel plated
Sealing ring	: Silicone
Gland body	: Brass with nickel plated
O-ring	: Silicone
Connection thread	: Metric (EN60423)/PG (DIN 40430)
Certificates	: ROHS, CE, PT, TUV, TÜRK LOYDU
Protection class	: IP68 - 5 bar
Temperature range	: -60 °C +180 °C

Properties

High low temperature resistance
Smooth surface
Easy to assemble



SİLİKON CANTALI ETANJ PİRİNÇ RAKOR

Hammaddesi	: Piring, nikel kaplı
Bağlantı dişi M	: EN 60423
Bağlantı dişi PG	: DIN 40430
Koruma sınıfı	: IP68 - 5 bar
Isıya direnci	: -60 °C + 180 °C
Conta	: Silikon
O-ring	: Silikon

METRIC/PG THREAD CABLE GLANDS

AG Thread	Code	H mm	GL mm	B mm	C mm	Ø mm	IP 68 Halogen free
M 12 x 1,5	MBGS 01	22	6	14	14	3 - 6,5	
M 16 x 1,5	MBGS 02	23	7	18	17	4 - 8	
M 20 x 1,5	MBGS 03	26,5	8	22	22	6 - 12	
M 25 x 1,5	MBGS 04	28	8	27	24	10 - 14	
M 32 x 1,5	MBGS 05	31,5	9	34	30	13 - 18	
M 40 x 1,5	MBGS 06	38	9	43	40	18 - 25	
M 50 x 1,5	MBGS 07	43	9	55	50	22 - 32	
M 63 x 1,5	MBGS 08	48	14	68	64	34 - 44	
PG 7	PBGS 01	22	6	14	14	3 - 6,5	
PG 9	PBGS 02	23	6	17	17	4 - 8	
PG 11	PBGS 03	24,5	6	20	20	5 - 10	
PG 13,5	PBGS 04	26,5	6,5	22	22	6 - 12	
PG 16	PBGS 05	28	6,5	24	24	10 - 14	
PG 21	PBGS 06	31,5	7	30	30	13 - 18	
PG29	PBGS 07	38	8	40	40	18 - 25	
PG36	PBGS 08	43	10	50	50	22 - 32	
PG42	PBGS 09	47	12	57	57	30 - 38	
PG48	PBGS 10	48	14	64	64	34 - 44	

PRODUCT RANGE OVERVIEW