

ORTAC PLASTIC CABLE GLANDS SERIES




EX POLYAMIDE CABLE GLANDS  
STANDARD TYPE PG

EXO SERIES

TECHNICAL DETAILS

Type	: ExO Series (Polyamide Ex-proof gland)
Protection code	: II 2G Ex eb IIC Gb II 2D Ex tb IIIC Db
Certificate	: IEP 20 ATEX 0750 X ATEX, ROHS, CE, PT, TUV
Gland body	: Polyamide PA6
Connection thread	: PG (DIN 40430)
Colour	: Black (RAL 9005) - Blue (RAL 5015) Black Blue (RAL 9005 - RAL 2015)
Standarts	: EN 60079-0, 60079-7, 60079-31
Protection class	: IP68 5 Bar
Temperature range	: -30 °C +100 °C
Application area	: ZONE1, ZONE2, ZONE21, ZONE22, Gas Group IIA, IIB, IIC
Cable type	: Unarmoured



ZIRHSIZ EX-PROOF ETANJ RAKOR

Hammaddesi	: Polyamid PA6
Renk	: RAL 9005 (Siyah) : RAL 5015 (Mavi)
Bağlantı dışı P	: DIN 40430
Koruma sınıfı	: IP68 5 bar
Sürekli ısıya direnci	: -30 °C + 100 °C

METRIC THREAD CABLE GLANDS

AG Thread	Black Code ■ RAL 9005	Blue Code ■ RAL 5012	Black - Blue Code ■ RAL 9005 ■ RAL 5012	H mm	GL mm	mm	mm
PG-7	ExOXXORB 01	ExOXXORM 01	ExOXXORMB 01	24	8	15	3 - 6,5
PG-9	ExOXXORB 02	ExOXXORM 02	ExOXXORMB 02	28	8	19	4 - 8
PG-11	ExOXXORB 03	ExOXXORM 03	ExOXXORMB 03	29	8	22	5 - 10
PG-13.5	ExOXXORB 04RS	ExOXXORM 04RS	ExOXXORMB 04RS	29	9	24	4 - 10
PG-13.5	ExOXXORB 04	ExOXXORM 04	ExOXXORMB 04	29	9	24	6 - 12
PG-16	ExOXXORB 05	ExOXXORM 05	ExOXXORMB 05	33	9	27	10 - 14
PG-21	ExOXXORB 06	ExOXXORM 06	ExOXXORMB 06	38	11	33	13 - 18
PG-21	ExOXXORB 06/9-17	ExOXXORM 06/9-17	ExOXXORMB 06/9-17	38	11	33	9 - 17
PG-29	ExOXXORB 07	ExOXXORM 07	ExOXXORMB 07	41	11	42	18 - 25
PG-36	ExOXXORB 08	ExOXXORM 08	ExOXXORMB 08	51	13	53	22 - 32
PG-42	ExOXXORB 09	ExOXXORM 09	ExOXXORMB 09	53	13	60	30 - 38
PG-48	ExOXXORB 10	ExOXXORM 10	ExOXXORMB 10	55	14	65	34 - 44

LONG THREAD PG CABLE GLANDS

PG-7	ExOXXORBL 01	ExOXXORML 01	ExOXXORMBL 01	24	15	15	3 - 6,5
PG-9	ExOXXORBL 02	ExOXXORML 02	ExOXXORMBL 02	28	15	19	4 - 8
PG-11	ExOXXORBL 03A	ExOXXORML 03A	ExOXXORMBL 03A	29	10	22	5 - 10
PG-11	ExOXXORBL 03	ExOXXORML 03	ExOXXORMBL 03	29	15	22	5 - 10
PG-13.5	ExOXXORBL 04RS	ExOXXORML 04RS	ExOXXORMBL 04RS	29	15	24	4 - 10
PG-13.5	ExOXXORBL 04	ExOXXORML 04	ExOXXORMBL 04	29	15	24	6 - 12
PG-16	ExOXXORBL 05	ExOXXORML 05	ExOXXORMBL 05	33	15	27	10 - 14
PG-21	ExOXXORBL 06	ExOXXORML 06	ExOXXORMBL 06	38	15	33	13 - 18
PG-21	ExOXXORBL 06/9-17	ExOXXORML 06/9-17	ExOXXORMBL 06/9-17	38	15	33	9 - 17

PRODUCT RANGE OVERVIEW

IP 68

Halogen free